ACN 130 955 725

First Floor, 768 Canning Highway, Applecross, Western Australia 6153

PO Box 1725, Applecross, Western Australia 6953

P: +61 8 9315 9009

F: +61 8 9315 5004

www.hotchili.net.au



ASX Announcement

Thursday 20th June 2019

Cortadera Delivers One of the Worlds Standout Copper-Gold Porphyry Drill Results

Highlights

 Hot Chili records a standout diamond drill result, confirming the discovery of a new, large, high grade zone at depth on the main porphyry of the Cortadera copper-gold discovery in Chile

CRP0013D

622m grading 0.6% copper and 0.2g/t gold from 204m depth including a New High Grade Zone comprising:

188m grading 0.9% copper and 0.4g/t gold from 516m depth which includes:

100m grading 1.0% copper and 0.5g/t gold from 530m depth

(including significant silver and molybdenum)

- CRP0013D has been terminated early at 1,185.9m vertical depth in mineralised porphyry, with assay results pending for the remaining 359.9m of the hole
- In addition, results for CRP0012D confirm a significant northern extension to the main porphyry, now drill defined over 600m in strike length, 220m in average width and remaining largely open both laterally and vertically

CRP0012D

200m grading 0.4% copper and 0.2g/t gold from 378m depth

- Variation to the Carola Option Agreement executed with SCM Carola to provide a 90 day extension to US\$3M of the first US\$5M payment
- Strategic funding discussions advancing with several large domestic and international groups

Hot Chili Limited (ASX code HCH) ("Hot Chili" or "Company") is pleased to confirm that it has recorded the best drilling intersection in the Company's history and the best result to date at its Cortadera copper project in Chile.

The result in CRP0013D is comparable to some of SolGold's (TSX/LSE: SOLG) early discovery drill results, which outlined the beginnings of a bulk tonnage, high grade zone at depth on its world-class Cascabel copper-gold deposit in Ecuador.

ASX CODE

HCH

Contact

Mr Christian Easterday Managing Director

E: admin@hotchili.net.au





ACN 130 955 725

First Floor, 768 Canning Highway, Applecross, Western Australia 6153

PO Box 1725, Applecross, Western Australia 6953

P: +61 8 9315 9009

F: +61 8 9315 5004

www.hotchili.net.au



Hot Chili's Managing Director Christian Easterday said the assay results from Hot Chili's first two diamond holes have transformed the Company's view of Cortadera, opening up large possibilities.

"We have achieved one of the worlds standout copper-gold porphyry drill intersections at Cortadera; one that is comparable to some of the best discovery drill results of recent times.

"At an average grade of 0.9% copper and 0.4 g/t gold, the new high grade zone currently has a vertical extent of approximately 190m.

"What is really exciting is that this new high grade zone is completely open in all directions at depth, and is similar in combined average grade and depth to SolGold's high grade zone at its world-class Cascabel discovery in Ecuador.

"The result in CRP0013D demonstrates that Cortadera has the potential to become a company-maker in its own right and looks set to take centre stage ahead of our Productora project, located 14km away.

"We are now pausing our drilling activities while we await remaining assay results for CRP0013D, and plan the next steps towards commencement of a second phase of drilling and a preliminary resource estimation at Cortadera" Easterday said.

First Diamond Results Deliver Immediate Growth

Hot Chili has received assay results for the first two diamond (DD) holes completed into the largest of four porphyries (Cuerpo 3) discovered to date at the Cortadera copper-gold discovery in Chile.

The DD holes were designed to test large potential upside recognised at Cuerpo 3, namely:

- 1. Strike extensional potential, and
- 2. The potential for an increasing grade profile with depth

The first DD hole (CRP0012D) tested the northwest strike extent of the Cuerpo 3 porphyry. The hole was successful in recording a wide intersection of porphyry from much deeper downhole than expected (and further north than expected). Assays now received confirm this:

200m grading 0.4% copper and 0.2g/t gold from 378m depth

including

76m grading 0.5% copper and 0.2g/t gold from 494m depth

Mineralisation remains open towards the north and northwest indicating the Cuerpo 3 porphyry is at least 600m in strike extent and approximately 220m average width.



ACN 130 955 725

First Floor, 768 Canning Highway, Applecross, Western Australia 6153

PO Box 1725, Applecross, Western Australia 6953

P: +61 8 9315 9009

F: +61 8 9315 5004

www.hotchili.net.au



The second hole (CRP0013D) tested the extent of a potential higher grade core at Cuerpo 3, where previous work had highlighted an increasing grade profile with depth (evident for copper, gold, silver and molybdenum).

CRP0013D has just been completed to a depth of 1,185.9m and ended in mineralised porphyry. The hole was terminated early owing to technical risk associated with the hole condition.

Assay results received for the first 826m of CRP0013D have delivered an outstanding drill intersection, exceeding the Company's expectations and outlining the discovery of a new high grade zone commencing from 516m vertical depth as follows:

622m grading 0.6% copper and 0.2g/t gold from 204m depth including a new high grade zone comprising:

188m grading 0.9% copper and 0.4g/t gold from 516m depth which includes:

100m grading 1.0% copper and 0.5g/t gold from 530m depth

(including significant silver and molybdenum)

The drilling intersection confirms the presence of a broad zone of high grade copper and gold mineralisation (0.9% copper and 0.4g/t gold) below the previous depth extent of historical DD drilling and is expected to grow with the receipt of the remaining 359.9m of assay results for CRP0013D.

The new high grade zone extends for 188m vertically and is related to high vein abundance, elevated magnetite alteration and high sulphide content in association with strong chalcopyrite content (both disseminated and vein hosted) and minor molybdenite. The majority of vein orientations are generally at a moderate to high angle-to-core, indicating that the high grade zone is likely to be close to true width.

At a depth of 890m until 990m, following 64m of mineralised porphyry below the preliminary drill intersection outlined above, CRP0013D intersects a zone of late-stage barren and poorly mineralised porphyry dykes. Following this zone, the remainder of CRP0013D has intersected moderately mineralised porphyry to end of hole. Assay results are outstanding between 826m and 1,185.9m depth.

The Company has commenced a detailed review of recently secured historical information (as announced to ASX on 12th June 2019) in combination with the Company's own drilling data.

Preliminary modelling of Cuerpo 1, 2 and 3 has highlighted a much larger porphyry system than first recognised, but more importantly, exhibiting many characteristics that suggest Cortadera has the potential to get even larger.

The following figures 1, 2, 3, and 4 display the location of the recent significant intersections at Cortadera in plan, long section and cross section view.

Several core photographs are also provided in figure 5 displaying typical alteration, vein style and sulphide mineralisation associated with higher grades encountered in CRP0013D.



ACN 130 955 725

First Floor, 768 Canning Highway, Applecross, Western Australia 6153

PO Box 1725, Applecross, Western Australia 6953

P: +61 8 9315 9009

F: +61 8 9315 5004

www.hotchili.net.au






Figure 1 Plan view across the Cortadera discovery area displaying significant historical copper-gold DD intersections across Cuerpo 1, 2, 3 and 4 tonalitic porphyry intrusive centres. Note the location of Type Sections A, and the inset plan are for Cuerpo3 associated with the following figures

ACN 130 955 725

First Floor, 768 Canning Highway, Applecross, Western Australia 6153


PO Box 1725, Applecross, Western Australia 6953

P: +61 8 9315 9009

F: +61 8 9315 5004

www.hotchili.net.au





For personal

Figure 2 Long Section looking north across Cuerpo 1, 2, 3 and 4 at the Cortadera copper-gold discovery. Note the location of CRP0013D which has identified a significant new high grade zone at depth within the main porphyry – Cuerpo 3

ACN 130 955 725

First Floor, 768 Canning Highway, Applecross, Western Australia 6153

PO Box 1725, Applecross, Western Australia 6953

P: +61 8 9315 9009

F: +61 8 9315 5004






Figure 3 Type Section A displaying historical DD drill results and an interpretation of Cuerpo 3 - the main host tonalitic porphyry intrusion at Cortadera. CRP0013D has been completed to a vertical depth of 1,185.9m with the last 359.9m of assay results still pending receipt from this hole.



ACN 130 955 725

First Floor, 768 Canning Highway, Applecross, Western Australia 6153

PO Box 1725, Applecross, Western Australia 6953

P: +61 8 9315 9009

F: +61 8 9315 5004






Figure 4 Plan view of Cuerpo 3 - the Main porphyry of the four porphyry centres discovered to date at Cortadera. The plan displays the location and basic geology of the mineralised tonalitic host porphyry and the surrounding lower grade mineralised skarn halo. Note the location of significant new results released for CRP0012D CRP0013D



ACN 130 955 725

First Floor, 768 Canning Highway, Applecross, Western Australia 6153

PO Box 1725, Applecross, Western Australia 6953

P: +61 8 9315 9009

F: +61 8 9315 5004






Figure 5 Various core photos from CRP0013D for mineralised porphyry at Cuerpo 3, Cortadera copper-gold discovery. Note the high vein abundance, elevated magnetite alteration and high sulphide content in association with strong chalcopyrite and pyrite (both disseminated and vein hosted).

ACN 130 955 725

First Floor, 768 Canning Highway, Applecross, Western Australia 6153

PO Box 1725, Applecross, Western Australia 6953

P: +61 8 9315 9009

F: +61 8 9315 5004

www.hotchili.net.au



The Company looks forward to releasing final drill results from CRP0013D once all assays are received.

The Company also looks forward to providing an update in relation to key work streams and progress associated with its strategic funding discussions in the coming weeks ahead.

The Directors would like to thank SCM Carola for their co-operation in providing access for early drilling and flexibility on timing of the first Option payment for the acquisition of Cortadera (details of the Carola Option Agreement previously released to ASX on 25th February 2019).

In addition, the Directors would also like to thank our dedicated exploration and drilling team for their efforts in delivering this exceptional result.

For more information please contact:

Christian Easterday +61 8 9315 9009

Managing Director Email: christian@hotchili.net.au

or visit Hot Chili's website at www.hotchili.net.au

Table 1 Significant DD Drill Results at Cortadera

| _ | | | | | <u> </u> | | | | | | | | | |
|---|----------|-----------------|-----------|------|----------|-----|--------|--------|--------|----------|--------|-------------|-------------|------------|
| | | Cod | ordinates | | | | Hole | Inters | ection | Interval | Copper | Gold | Silver | Molybdenum |
| | Hole_ID | North | East | RL | Azim | Dip | Depth | From | То | (m) | (% Cu) | (g/t Au) | (ppm Ag) | (ppm Mo) |
| | CRP0012D | 6814039 | 336224 | 1017 | 44 | -60 | 666.6 | 378 | 578 | 200 | 0.4 | 0.2 | 0.7 | 116 |
| 4 | | including | | | | | | 494 | 570 | 76 | 0.5 | 0.2 | 0.9 | 205 |
| | CRP0013D | 6814070 | 336348 | 1020 | 360 | -90 | 1185.9 | 204 | 826 | 622 | 0.6 | 0.2 | 1.2 | 79 |
| 5 | | including | | | | | | 516 | 704 | 188 | 0.9 | 0.4 | 1.7 | 94 |
| |) | or including | | | | | | 530 | 630 | 100 | 1.0 | 0.5 | 2.4 | 96 |

Note: Results pending for remaining 359.9m of CRP0013D



ACN 130 955 725

First Floor, 768 Canning Highway, Applecross, Western Australia 6153

PO Box 1725, Applecross, Western Australia 6953

P: +61 8 9315 9009

F: +61 8 9315 5004

www.hotchili.net.au



About Cortadera

Cortadera is a privately-owned, major copper-gold porphyry discovery located along the Chilean coastal range, where historical world-class discovery drill results have only recently been publicly released by Hot Chili.

Importantly, Cortadera lies 14km from the Company's large-scale Productora copper development and adjacent to the high grade El Fuego satellite copper projects, as displayed in Figure 1 below.




Figure 1 Location of Productora and the Cortadera discovery in relation to the consolidation of new growth projects and coastal range infrastructure

On 22nd February 2019, Hot Chili announced to the Australian Securities Exchange (ASX) the execution of a formal Option Agreement to acquire a 100% interest in Cortadera.

In early April, the Company commenced a confirmation drilling programme comprising 17 holes for approximately 5,000m of RC and 1,500m of DD drilling.

The drilling aims to confirm and extend areas of surface enrichment and wide, higher-grade, copper-gold sulphide mineralisation, which had not previously been closed off by 23,000m of historical diamond drilling.

Initial results from shallow RC drilling completed by Hot Chili have confirmed extensive copper from surface in addition to near-surface enrichment zones across Cuerpo 1 and 2 at Cortadera.

Diamond (DD) drilling is currently being completed across Cuerpo 3 (the largest of the four porphyries discovered to date) where previous DD drilling had recorded wide copper sulphide intersections which remained open (up-dip, down-dip and laterally), including:

864m grading 0.4% copper and 0.1g/t gold from 62m down-hole depth (including 348m grading 0.6% copper and 0.2g/t gold)

ACN 130 955 725

First Floor, 768 Canning Highway, Applecross, Western Australia 6153


PO Box 1725, Applecross, Western Australia 6953

P: +61 8 9315 9009

F: +61 8 9315 5004

www.hotchili.net.au





198m grading 0.6% copper and 0.2g/t gold from 652m down-hole depth

Combining Productora and Cortadera to leverage central processing and infrastructure, looks likely to underpin a globally significant new copper development along the coastline of Chile.



Qualifying Statements

JORC Compliant Ore Reserve Statement

Productora Open Pit Probable Ore Reserve Statement – Reported 2nd March 2016

| | _ | Tonnage | | Grade | | | Contained | Metal | | Payable Metal | | |
|--------------|---------------------|---------|------|-------|-------|----------|-----------|------------|----------|---------------|------------|--|
| Ore Type | Reserve Category | Tomage | Cu | Au | Mo | Copper | Gold | Molybdenum | Copper | Gold | Molybdenum | |
| | category | (Mt) | (%) | (g/t) | (ppm) | (tonnes) | (ounces) | (tonnes) | (tonnes) | (ounces) | (tonnes) | |
| Oxide | | 24.1 | 0.43 | 0.08 | 49 | 103,000 | 59,600 | 1,200 | 55,600 | | | |
| Transitional | Probable | 20.5 | 0.45 | 0.08 | 92 | 91,300 | 54,700 | 1,900 | 61,500 | 24,400 | 800 | |
| Fresh | | 122.4 | 0.43 | 0.09 | 163 | 522,500 | 356,400 | 20,000 | 445,800 | 167,500 | 10,400 | |
| Total | Probable | 166.9 | 0.43 | 0.09 | 138 | 716,800 | 470,700 | 23,100 | 562,900 | 191,900 | 11,200 | |

Note 1: Figures in the above table are rounded, reported to two significant figures, and classified in accordance with the Australian JORC Code 2012 guidance on Mineral Resource and Ore Reserve reporting. Note 2: Price assumptions: Cu price - US\$3.00/lb; Au price US\$1200/oz; Mo price US\$14.00/lb. Note 3: Mill average recovery for fresh Cu - 89%, Au - 52%, Mo - 53%. Mill average recovery for transitional; Cu 70%, Au - 50%, Mo - 46%. Heap Leach average recovery for oxide; Cu - 54%. Note 4: Payability factors for metal contained in concentrate: Cu - 96%; Au - 90%; Mo - 98%. Payability factor for Cu cathode - 100%.

JORC Compliant Mineral Resource Statements

Productora Higher Grade Mineral Resource Statement, Reported 2nd March 2016

| | | | Grad | de | | | Contained Meta | l |
|------------|----------------|---------|------|-------|-------|-----------|----------------|------------|
| | | Tonnage | Cu | Au | Mo | Copper | Gold | Molybdenum |
| Deposit | Classification | (Mt) | (%) | (g/t) | (ppm) | (tonnes) | (ounces) | (tonnes) |
| | Indicated | 166.8 | 0.50 | 0.11 | 151 | 841,000 | 572,000 | 25,000 |
| Productora | Inferred | 51.9 | 0.42 | 0.08 | 113 | 219,000 | 136,000 | 6,000 |
| | Sub-total | 218.7 | 0.48 | 0.10 | 142 | 1,059,000 | 708,000 | 31,000 |
| | Indicated | 15.3 | 0.41 | 0.04 | 42 | 63,000 | 20,000 | 600 |
| Alice | Inferred | 2.6 | 0.37 | 0.03 | 22 | 10,000 | 2,000 | 100 |
| | Sub-total | 17.9 | 0.41 | 0.04 | 39 | 73,000 | 23,000 | 700 |
| | Indicated | 182.0 | 0.50 | 0.10 | 142 | 903,000 | 592,000 | 26,000 |
| Combined | Inferred | 54.5 | 0.42 | 0.08 | 109 | 228,000 | 138,000 | 6,000 |
| | Total | 236.6 | 0.48 | 0.10 | 135 | 1,132,000 | 730,000 | 32,000 |

Reported at or above 0.25 % Cu. Figures in the above table are rounded, reported to two significant figures, and classified in accordance with the Australian JORC Code 2012 guidance on Mineral Resource and Ore Reserve reporting. Metal rounded to nearest thousand, or if less, to the nearest hundred.

Productora Low Grade Mineral Resource Statement, Reported 2nd March 2016

| | | | Grad | le | | | Contained Meta | |
|------------|----------------|---------|------|-------|-------|----------|----------------|------------|
| | | Tonnage | Cu | Au | Mo | Copper | Gold | Molybdenum |
| Deposit | Classification | (Mt) | (%) | (g/t) | (ppm) | (tonnes) | (ounces) | (tonnes) |
| | Indicated | 150.9 | 0.15 | 0.03 | 66 | 233,000 | 170,000 | 10,000 |
| Productora | Inferred | 50.7 | 0.17 | 0.04 | 44 | 86,000 | 72,000 | 2,000 |
| | Sub-total | 201.6 | 0.16 | 0.04 | 60 | 320,000 | 241,000 | 12,000 |
| | Indicated | 12.3 | 0.14 | 0.02 | 29 | 17,000 | 7,000 | 400 |
| Alice | Inferred | 4.1 | 0.12 | 0.01 | 20 | 5,000 | 2,000 | 100 |
| | Sub-total | 16.4 | 0.13 | 0.02 | 27 | 22,000 | 9,000 | 400 |
| | Indicated | 163.2 | 0.15 | 0.03 | 63 | 250,000 | 176,000 | 10,000 |
| Combined | Inferred | 54.8 | 0.17 | 0.04 | 43 | 91,000 | 74,000 | 2,000 |
| | Total | 218.0 | 0.16 | 0.04 | 58 | 341,000 | 250,000 | 13,000 |

Reported at or above 0.1% Cu and below 0.25 % Cu. Figures in the above table are rounded, reported to two significant figures, and classified in accordance with the Australian JORC Code 2012 guidance on Mineral Resource and Ore Reserve reporting. Metal rounded to nearest thousand, or if less, to the nearest hundred. Metal rounded to nearest thousand, or if less, to the nearest hundred.

Mineral Resource and Ore Reserve Confirmation

The information in this presentation that relates to Mineral Resources, Ore Reserve estimates and Production Targets on the Productora copper project was previously reported in the ASX announcement "Hot Chili Delivers PFS and Near Doubles Reserves at Productora" dated 2nd March 2016, a copy of which is available on the ASX website at www.asx.com.au and the Company's website at www.hotchili.net.au. The company confirms that it is not aware of any new formation or data that materially affects the information included in the original market announcement and that all material assumptions and technical parameters underpinning the estimates in that announcement continue to apply and have not materially changed. The Company confirms that the form and context in which the Competent Person's findings are presented have not been materially modified from the original market announcement

Competent Person's Statement- Exploration Results

Exploration information in this Announcement is based upon work compiled by Mr Christian Easterday, the Managing Director and a full-time employee of Hot Chili Limited whom is a Member of the Australasian Institute of Geoscientists (AIG). Mr Easterday has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a 'Competent Person' as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves' (JORC Code). Mr Easterday consents to the inclusion in the report of the matters based on their information in the form and context in which it appears.

Competent Person's Statement- Mineral Resources

The information in this Announcement that relates to the Productora Project Mineral Resources, is based on information compiled by Mr J Lachlan Macdonald and Mr N Ingvar Kirchner. Mr Macdonald is employed by AMC Consultants (AMC), and is a Member of the Australasian Institute of Mining and Metallurgy (AusIMM). Mr Kirchner is employed by AMC Consultants (AMC). AMC has been engaged on a fee for service basis to provide independent technical advice and final audit for the Productora Project Mineral Resource estimates. Mr Kirchner is a Fellow of the Australasian Institute of Mining and Metallurgy (AusIMM) and is a Member of the Australian Institute of Geoscientists (AIG). Both Mr Macdonald and Mr Kirchner have sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves' (the JORC Code 2012).

Competent Person's Statement- Ore Reserves

The information in this Announcement that relates to Productora Project Ore Reserves, is based on information compiled by Mr Carlos Guzmán, Mr Boris Caro, Mr Leon Lorenzen and Mr Grant King. Mr Guzmán is a Fellow of the Australasian Institute of Mining and Metallurgy (AusIMM), a Registered Member of the Chilean Mining Commission (RM- a 'Recognised Professional Organisation' within the meaning of the JORC Code 2012) and a full time employee of NCL Ingeniería y Construcción SpA (NCL). Mr Caro is a former employee of Hot Chili Ltd, now working in a consulting capacity for the Company, and is a Member of the Australasian Institute of Mining and Metallurgy (AusIMM) and a Registered Member of the Chilean Mining Commission. Mr Lorenzen is employed by Mintrex Pty Ltd and is a Chartered Professional Engineer, Fellow of Engineers Australia, and is a Fellow of the Australasian Institute of Mining and Metallurgy (AusIMM). Mr King is employed by AMEC Foster Wheeler (AMEC FW) and is a Member of the Australasian Institute of Mining and Metallurgy (AusIMM). NCL, Mintrex and AMEC FW have been engaged on a fee for service basis to provide independent technical advice and final audit for the Productora Project Ore Reserve estimate. Mr. Guzmán, Mr Caro, Mr Lorenzen and Mr King have sufficient experience which is relevant to the style of mineralisation and type of deposit under consideration, and to the activity which they are undertaking to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'.

Forward Looking Statements

This Announcement is provided on the basis that neither the Company nor its representatives make any warranty (express or implied) as to the accuracy, reliability, relevance or completeness of the material contained in the Announcement and nothing contained in the Announcement is, or may be relied upon as a promise, representation or warranty, whether as to the past or the future. The Company hereby excludes all warranties that can be excluded by law. The Announcement contains material which is predictive in nature and may be affected by inaccurate assumptions or by known and unknown risks and uncertainties and may differ materially from results ultimately achieved.

The Announcement contains "forward-looking statements". All statements other than those of historical facts included in the Announcement are forward-looking statements including estimates of Mineral Resources. However, forward-looking statements are subject to risks, uncertainties and other factors, which could cause actual results to differ materially from future results expressed, projected or implied by such forward-looking statements. Such risks include, but are not limited to, copper, gold and other metals price volatility, currency fluctuations, increased production costs and variances in ore grade recovery rates from those assumed in mining plans, as well as political and operational risks and governmental regulation and judicial outcomes. The Company does not undertake any obligation to release publicly any revisions to any "forward-looking statement" to reflect events or circumstances after the date of the Announcement, or to reflect the occurrence of unanticipated events, except as may be required under applicable securities laws. All persons should consider seeking appropriate professional advice in reviewing the Announcement and all other information with respect to the Company and evaluating the business, financial performance and operations of the Company. Neither the provision of the Announcement nor any information contained in the Announcement or subsequently communicated to any person in connection with the Announcement is, or should be taken as, constituting the giving of investment advice to any person

JORC Code, 2012 Edition – Table 1 report template

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

| _ | nis section apply to all succeeding sections.) | |
|------------------------|---|---|
| Criteria | JORC Code explanation | Commentary |
| Sampling techniques | Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma | This announcement updates activities at Hot Chili Limited's ("Hot Chili" or the "Company") Cortadera Project. This includes assay results from the current drilling programme being undertaken at the Cortadera copper-gold porphyry discovery. Reverse circulation drilling (RC) was used to produce a 1m bulk sample and representative 2m |
| | sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the | cone split samples (nominally a 12.5% split) were collected using a cone splitter. Geological logging was completed, and mineralised sample intervals were determined by the geologists to be submitted as 2m samples for RC drilling. In RC intervals assessed as unmineralised, 4m composite (scoop) samples were collected for laboratory for analysis. If these 4m composite samples return results with anomalous grade the corresponding original 2m split |
| | appropriate calibration of any measurement tools or systems used.Aspects of the determination of mineralisation | samples are then routinely submitted to the laboratory for analysis. |
| | that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg | The samples were crushed and split at the laboratory, with up to 3kg pulverised, with a 50g samples analysed by Industry standard methods. |
| | 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In | The sampling techniques used are deemed appropriate for exploration and resource development purposes for this type of mineralisation. |
| | other cases more explanation may be required, such as where there is coarse gold | The data compiled for historical drilling at the Cortadera project has been collated from SCM Carola documents. |
| | that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information. | Historical drilling at the Cortadera project is diamond core (DD). There have been 29 diamond holes drilled for a total of 19,268m. A further 10 diamond holes for a further 3,963m has been completed along-strike at Purisima |
| | | Historical and Hot Chili diamond sampling was predominantly HQ3 (61.24mm) half core. 99% of the sample data is comprised of 2m composited samples (which were taken at every 2m interval). |
| | | These results comprise 30g fire assay for gold, and for copper, either 4-acid or 3-acid digest followed by either an ICP-MS, ICP-AAS or HF-ICP-AES. |
| | | Hot Chili Limited ("the Company") has verified as much as possible the location, orientation, splitting and sampling methods, analytical techniques, and assay values. The Company has not |

| Criteria | JORC Code explanation | Commentary |
|--------------------------|--|---|
| | | completed a comprehensive review of the SCM Carola QA/QC data but notes that a substantial amount of QAQC data is available for review and the Company has undertaken a high level initial review of the SCM Carola QA/QC data. |
| Drilling techniques | Drill type (eg core, reverse circulation, open- hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face- | Hot Chili's Reverse Circulation drilling used 140 to 130mm diameter drill bits. RC drilling employed face sampling hammers ensuring contamination during sample extraction is minimised. |
| | sampling bit or other type, whether core is oriented and if so, by what method, etc). | Historical and Hot Chili diamond drilling used HQ bits (HQ; 96mm external, 61.24mm internal). |
| Drill sample recovery | Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximize comple recovery. | Drilling techniques to ensure adequate RC sample recovery and quality included the use of "booster" air pressure. Air pressure used for RC drilling was 700-800psi. |
| | Measures taken to maximise sample recovery and ensure representative nature of the samples. | All DD drilling undertaken utilised HQ core with sampling undertaken vai half core cutting and 2m sample intervals, aligned with historical DD sampling and drilling techniques. |
| | Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. | Logging of all samples followed established company procedures which included recording of qualitative fields to allow discernment of sample reliability. This included (but was not limited to) recording: sample condition, sample recovery, sample method. |
| | | The initial drilling programme is now complete and a final assessment of sample recovery and condition is planned to be undertaken. The majority of drilling has had no material recovery issues. |
| | | No quantitative analysis of samples weights, sample condition or recovery has been undertaken. |
| | | Twinned drilling analysis has been undertaken at the project to compare RC versus historical HQ diamond drilling. No significant variance has been identified. |
| | | Historical diamond drilling recovery has not been quantitatively assessed. A preliminary inspection of core photography was undertaken, and no material issues were noted. |
| | | Methods taken to maximise historical sample recovery, quality, condition are not known. |
| | | No analysis of historical samples weights, sample condition or recovery has been undertaken. |

| Criteria | JORC Code explanation | Commentary |
|--|---|---|
| Logging | Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. The total length and percentage of the relevant intersections logged. | Geological logging of samples followed established company and industry common procedures. Qualitative logging of samples included (but was not limited to) lithology, mineralogy, alteration and weathering. Every metre (100%) of HCH drilling was geologically logged. The total length of the relevant mineralised interval(s) is provided in the main body of the report. Geological logs have been provided as part of third-party historical data, these have been reviewed and are deemed to be of an appropriate standard. All geological logs are fully available and Hot Chili has also completed verification and re-logging programme of historical diamond drill core where required |
| Sub-sampling techniques and sample preparation | If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all subsampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the material being sampled. | Splitting of RC samples occurred via cone splitter by the RC drill rig operators. Cone splitting of RC drill samples occurred regardless of the sample condition. RC drilling sample weights range from 0.3kg to 7.0kg, but typically between 2-4kg, and generally averaging around 3.2kg. Half core 2m sample intervals have been utilised for Hot Chill's HQ diamond core, in-line with previous historical diamond core sampling All samples were submitted to ALS Coquimbo (Chile) for multi-element analysis. The sample preparation included: Samples were then split via rotatory splitter to achieve ~1kg split, - This split was then pulverised such that a minimum of 85% passes 75um and 150g was used for analytical pulp (ICP-AES), also 30g was used for fire assay fusion (gold). - 150g pulps derived from sample preparation (outlines in the previous sections) were used for multi-element analysis. ALS method ME-ICP61 involves a 4-acid digestion (Hydrochloric-Nirtic-Perchloric-Hydrofluoric) followed by ICP-AES determination. - Samples that returned Cu grades >10,000ppm were analysed by ALS "ore grade" method Cu-OG62, which is a 4-acid digestion, followed by AES measurement to 0.001%Cu - Samples determined to be either oxide or transitional in weathering were also analysed using a copper soluble method Cu-AA05 |

| Criteria | JORC Code explanation | Commentary |
|---|---|---|
| | | Pulp samples were subsequently analysed for gold by ALS method Au-ICP21; a 30g lead-collection Fire Assay, followed by ICP-OES to a detection limit of 0.001ppm Au. |
| | | Sample collection, size and analytical methods are deemed appropriate for the style of exploration. |
| | | Historical Half diamond core was sampled. All samples were submitted to either ACTLABS (Chile), ACME Labs (now Bureau Veritas, Chile), ALS Global (Chile) or Andes Analytical Assay (Chile). |
| | | Hot Chili Limited has verified the historical sampling methods, analytical techniques, and assay values. The Company has undertaken a high-level initial review of the SCM Carola QA/QC data. |
| | | The lab specific methods used at the time of historical drilling are yet to be confirmed, and will be verified as part of the Company's due diligence. |
| | | Sample length collection methods of historical diamond sampling are considered acceptable for the exploration of these styles of mineralisation. |
| Quality of assay data and laboratory | The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. | laboratories in Chile (ALS Coquimbo). Typical analysis methods are detailed in the previous |
| tests | For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and | Hot Chili undertakes several steps to ensure quality of sampling. These include, but are not limited to, the use of duplicates, certified reference material and blank media: Routine 'standard' (mineralised pulp) Certified Reference Material (CRM) was inserted at a nominal rate of 1 in 50 samples. Routine 'blank' material (mineralised quartz) was inserted at a nominal rate of 1 in 100 samples at the logging geologist's discretion. Routine field duplicates for RC samples were submitted at a rate of 1 in 50 samples. The drilling programme is still underway, and while the full analysis of quality parameters has yet to be undertaken, no significant issues have been noted. |
| | precision have been established. | No umpire checks were undertaken by Hot Chili during this period. The analytical laboratories provided their own routine quality controls within their own practices. No significant issues have been noted. |
| | | All historical Cortadera samples were assayed by industry standard methods through commercial laboratories in Chile (ACTLABS, ALS Global, or Andes Analytical Assay). |

| Criteria | JORC Code explanation | Commentary |
|---|---|---|
| | | Typical analysis methods used for historical samples included; For copper and multi-element; either 4-acid or 3-acid digest followed by either an ICP-MS, ICP-AAS, or a HF digest with ICP-AES. E.g. ACTLAB method 3ACID-AAS, ALS method Cu-AA61, Andes Analytical Assay method (4A-AAS1E01 or ICP_AES_HH22). Gold grades were analysed for Fire Analysis (30g charge). E.g. ACTLABS method FA-AAS, ALS method Au-AA23, Andes Analytical Assay method AEF_AAS1EE9. No formal assessment of SCM Carola standards, duplicates or umpire testing has been undertaken. Although a high level assessment of all assays which includes approximately 10% QAQC samples has been undertaken. No assessment of laboratories standards and practices has been undertaken for historical drilling. |
| Verification of sampling and assaying | The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. | The SCM Carola documents indicate that there has been some previous umpire sample test work. Hot Chili has not quantitatively reviewed this data. Hot Chili has commenced a programme of quarter core sampling across selected intervals of historical half diamond core Twinned drilling at the Cortadera project has commenced to compare RC to previous HC diamond drilling. One twin drill hole is expected to be completed at each of the three porphyry bodies defined (Purisima, Cuerpo 2 and Cuerpo 3) All retained core and pulp samples are stored in a secured site and are available for verification if required. |
| Location of data points | Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. | RC drill collars were set out using a hand help GPS and final collars were collected using a handheld GPS. The WGS84 UTM zone 19S coordinate system was used for all undertakings. Downhole surveys for RC drilling by Hot Chili were completed by the drilling contractor using a north-seeking gyroscope. Holes without downhole survey use planned or compass bearing/dip measurements for survey control. Drill collar survey methods undertaken by SCM Carola are yet to be verified, however all collars were located by Hot Chili and have been surveyed using a DGPS. Downhole surveys were completed on some of the Cortadera drilling. Holes without downhole survey use planned or compass bearing/dip measurements for survey control. |

| Criteria | JORC Code explanation | Commentary |
|---|--|---|
| Data spacing and distribution | Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied. | The PSAD56 zone 19S coordinate system was used for all Cortadera undertakings The spacing and location of the majority of the historical diamond drilling at the Cortadera project is variable and ranges from approximately 80m to 300m. Sampling has been undertaken at 2m intervals. The spacing and location of data is currently only being considered for exploration purposes with additional RC and diamond drilling being undertaken by Hot Chili to establish a Mineral Resource. |
| Orientation of data in relation to geological structure | Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. | Historical drilling completed and current drilling being completed at Cortadera is nominally perpendicular to mineralisation where practical and where known. The relationship of mineralisation widths to the intercepts of drilling undertaken by other previous companies is unknown and yet to be assessed, however copper-gold porphyry mineralisation is typically fairly homogenous meaning a limited chance of bias likely to be caused from drilling orientation. A list of the drill holes and orientations is stated in section 2 of this table for all historical diamond drilling and a list of drill holes reported in this announcement is contained within the body of this announcement. |
| Sample security | The measures taken to ensure sample security. | Considering the types of mineralisation at the Cortadera projects, the drilling orientations and subsequent sampling is considered to be unbiased in its representation for exploration reporting purposes. Hot Chili has strict chain of custody procedures that are adhered. All samples have the sample submission number/ticket inserted into each bulk polyweave sample bag with the id number clearly visible. The sample bag is stapled together such that no sample material can spill out and no one can tamper with the sample once it leaves Hot Chili's custody. The measures taken to ensure sample security during historical drilling are unknown. All retained core and pulp samples are currently stored in a secured site and are available for verification if required. |
| Audits or reviews | The results of any audits or reviews of sampling techniques and data. | None completed. |

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

| Criteria | JORC Code explanation | Commen | tary | | | | | | | |
|--|---|--|--------------|---------------|------------|------------------------|-------------|-------|-------------------------|-------------|
| Mineral | Type, reference name/number, location and | Cortadera | a Project te | nements ar | nd detail | s: | | | | |
| tenement and | ownership including agreements or material | Magdal | enita 1/2 | 20 | Corro | teo 5 1/2 | 61 | L | as Cañas 1 _/ | ' 15 |
| land tenure | issues with third parties such as joint | Atacam | ita 1/82 | | Pauli | na 27 A 1 _/ | ′30 | С | ortadera 1, | /40 |
| status | ventures, partnerships, overriding royalties, native title interests, historical sites, | Paulina | 11B 1/3 | 0 | Pauli | na 15 B 1/ | ′30 | P | aulina 24 A | 1/24 |
| | wilderness or national park and environmental | Paulina | 10B 1/2 | 0 | Pauli | na 22 A 1, | ′30 | P | aulina 25 A | 1/20 |
| | settings. The security of the tenure held at the time of | Amalia | 942 A 1/ | 10 | Corta | dera 1 1/ | 200 | | as Cañas Es /30 | ste 2003 |
| | reporting along with any known impediments to obtaining a licence to operate in the area. | Paulina | 12B 1/3 | 0 | Corta | dera 2 1/ | 200 | P | aulina 26 A | 1/30 |
| | to obtaining a needee to operate in the area. | Paulina | 13B 1/3 | 0 | Corta | dera 41 | | С | ortadera 42 | 2 |
| | | Paulina | 14B 1/3 | 0 | Corro | teo 1 1/2 | 80 | L | o Cañas 16 | |
| Exploration done by other parties Geology | Acknowledgment and appraisal of exploration by other parties. Deposit type, geological setting and style of mineralisation. | Paulina 14B 1/30 Corroteo 1 1/280 Lo Cañas 16 Previous exploration at the project included: - Historical surface workings - 1990's. Mount Isa Mining Company Chile undertook mapping, trench sampling, some geophysical surveying and limited drilling. - 2001. SCM Carola undertook field surveys including sampling. 2011-2012. Minera Fuego undertook surface mapping, drilling and surface sampling The Cu-Au-Mo mineralisation at Cortadera is associated with multiple porphyry intrusions. These porphyries have intruded into the early to mid Cretaceuos Totorralillo and Nantoco Formations (variously stratified chemical sediments, volcaniclastics, bioclastics, volcanic breccias, and andesitic volcanic units) along an apparent NW structure. These porphyries appear to exhibit typical Cu-Au porphyry veining networks and associated alteration styles. As typical in porphyry deposits, Cu and Au are strongly related, and higher-grade Cu and Mo are associated with high vein density. Local oxide mineralisation encountered in drilling and observed at surface suggests supergene | | | | | | | | |
| Drill hole Information | A summary of all information material to the understanding of the exploration results including a tabulation of the following | The coord | dinates and | d orientatior | ns for all | of the histo | orical Cort | adera | drill holes are | e provided |
| | information for all Material drill holes: | hole_id | easting | northing | RL | Datum | azimuth | dip | hole_depth | |
| | easting and northing of the drill hole collar elevation or RL (Reduced Level – elevation | FJOD-01 | 335750.0 | 6814312.0 | 977.2 | PSAD56 | 180 | -60 | 300.7 | |
| | above sea level in metres) of the drill hole | FJOD-02 | 335743.3 | 6814316.0 | 976.9 | PSAD56 | 225 | -69 | 542.6 | |
| | collar o dip and azimuth of the hole | FJOD-03 | 335598.1 | 6814752.7 | 1015.5 | PSAD56 | 315 | -70 | 323.1 | |

| Criteria | JORC Code explanation | Commen | itary | | | | | | |
|----------|---|--------------------|----------------------|------------------------|----------------|------------------|------------|------------|----------------|
| | down hole length and interception depth | | <u> </u> | 604 (272 | 40:05 | | | | |
| | o hole length. | FJOD-04 | 337169.0 | 6814370.0 | 1212.0 | PSAD56 | 350 | -60 | 278.0 |
| | If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract | FJOD-05 | 334476.8 | 6814324.5 | 916.9 | PSAD56 | 350 | -75 | 511.5 |
| | | FJOD-06 | 335629.0 | 6814182.1 | 994.5 | PSAD56 | 46 | -49 | 587.9 |
| | from the understanding of the report, the | FJOD-07 | 335873.7 | 6814350.8 | 985.4 | PSAD56 | 225 | -48 | 514.8 |
| | Competent Person should clearly explain why this is the case. | FJOD-08 | 335735.0 | 6814413.7 | 980.2 | PSAD56 | 224 | -70 | 589.9 |
| | | FJOD-09 | 336539.9 | 6813972.9 | 1034.5 | PSAD56 | 271 | -49 | 630.7 |
| | | FJOD-10 FJOD-11 | 335296.7 335201.2 | 6814717.2 6814625.9 | 961.1 959.5 | PSAD56 PSAD56 | 227 227 | -60 -50 | 536.2 451.9 |
| | | FJOD-11 | 335663.7 | 6814454.5 | 983.4 | PSAD56 | 227 | -55 | 248.0 |
| | | FJOD-13 | 336111.3 | 6814383.4 | 1007.4 | PSAD56 | 227 | -60 | 623.4 |
| | | FJOD-14 | 335667.2 | 6814457.7 | 983.5 | PSAD56 | 227 | -55 | 600.0 |
| | | FJOD-15 | 336274.7 | 6814265.6 | 1029.6 | PSAD56 | 227 | -60 | 712.9 |
| | | FJOD-16 | 336440.3 | 6814154.7 | 1043.3 | PSAD56 | 227 | -65 | 710.4 |
| | | FJOD-17 | 336488.7 | 6813913.6 | 1034.9 | PSAD56 | 227 | -65 | 599.3 |
| | | | | | | | | | |
| | | FJOD-18 | 336644.4 | 6813840.6 | 1045.3 | PSAD56 | 227 | -60 | 629.4 |
| | | FJOD-19 | 335591.6 | 6814752.6 | 1015.2 | PSAD56 | 54 | -78 | 1123.4 |
| | | FJOD-20 | 335553.2 | 6814353.5 | 966.2 | PSAD56 | 102 | -60 | 697.9 |
| | | FJOD-21 | 335114.7 | 6814659.9 | 961.0 | PSAD56 | 109 | -74 | 350.3 |
| | | FJOD-22 | 336190.0 | 6814175.5 | 1006.0 | PSAD56 | 30 | -60 | 631.3 |
| | | FJOD-23 | 336191.4 | 6813924.8 | 1027.3 | PSAD56 | 48 | -65 | 1007.0 |
| | | FJOD-24 | 335027.2 | 6814621.1 | 970.4 | PSAD56 | 110 | -75 | 250.8 |
| | | FJOD-25 | 334956.0 | 6814633.1 | 970.6 | PSAD56 | 110 | -75 | 281.4 |
| | | FJOD-26 | 335001.4 | 6814553.8 | 953.4 | PSAD56 | 110 | -70 | 98.7 |
| | | FJOD-27 | 334996.7 | 6814552.3 | 953.4 | PSAD56 | 290 | -75 | 191.6 |
| | | FJOD-28 | 335260.9 | 6814125.9 | 974.6 | PSAD56 | 305 | -70 | 545.7 |
| | | FJOD-29 | 336493.4 | 6813914.7 | 1035.0 | PSAD56 | 45 | -75 | 715.2 |
| | | FJOD-30 | 336192.2 | 6814169.4 | 1006.2 | PSAD56 | 45 | -80 | 713.4 |
| | | FJOD-31 | 336805.8 | 6813742.7 | 1059.9 | PSAD56 | 227 | -60 | 728.1 |
| | | FJOD-32 | 336198.0 | 6813922.3 | 1027.4 | PSAD56 | 90 | -65 | 1085.6 |

| Criteria | JORC Code explanation | Commentary |
|---|---|---|
| | | FJOD-33 335631.8 6814180.8 994.4 PSAD56 45 -68 947.2 |
| | | FJOD-34 335201.1 6814623.6 959.6 PSAD56 45 -70 647.3 |
| | | FJOD-35 335915.0 6814060.0 1024.0 PSAD56 45 -70 845.2 |
| | | FJOD-36 336303.0 6813740.0 1058.0 PSAD56 90 -70 1025.5 |
| | | FJOD-37 335372.0 6814431.0 951.0 PSAD56 45 -70 1000.0 |
| | | FJOD-38 335125.0 6814675.0 956.0 PSAD56 270 -60 446.5 |
| | | FJOD-39 336942.0 6813225.0 1150.0 PSAD56 0 -90 743.5 |
| | | All drill holes completed by Hot Chili have been reported in this announcement and previous announcements to the ASX made on 5 th June 2019 and 9 th May 2019. Any quoted results in the main report body, from historic or previous company drilling or sampling programmes, has been provided for historic and qualitative purposes only. All historic or previous company drilling results not included may be due to; a) uncertainty of result, location or other unreliability, b) yet to be assessed by Hot Chili, c) unmineralised, d) unsampled or unrecorded, or e) not considered material. |
| Data aggregation methods | In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values should be clearly stated. | In reported exploration results, length weighted averages are used for any non-uniform intersection sample lengths. Length weighted average is (sum product of interval x corresponding interval assay grade), divided by sum of interval lengths and rounded to one decimal place. |
| | | No top cuts have been considered in reporting of grade results, nor was it deemed necessary for the reporting of significant intersections. |
| | | No metal equivalent values have been reported. |
| Relationship between mineralisation widths and | These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its | Drilling at the Cortadera project was nominally perpendicular to mineralisation, where known and practical. The relationship of mineralisation widths to the intercepts of drilling undertaken by other previous |
| | nature should be reported. | companies is unknown and is currently being assessed. |

| Criteria | JORC Code explanation | Commentary |
|---|---|---|
| intercept lengths | If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). | |
| Diagrams | Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. | Refer to figures in announcement. A plan view of reported significant intersection drill holes are included. |
| Balanced reporting | Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results. | It is not practical to report all exploration results as such unmineralised intervals. Low or non-material grades have not been reported, however a full list of drill hole coordinate and orientation details is stated above. |
| | | All drill hole locations are reported and a table of significant intervals is provided in the announcement. |
| Other substantive exploration data | Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances. | Available data from historic or previous exploration parties includes some surface mapping, surface geochemical surveys and geophysical surveys (Ground magnetics, airborne magnetics and Induced Polarisation surveys. Where possible, historic exploration data has been supported by selected sampling and geological mapping undertaken by Hot Chili. |
| Further work | The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. | Potential work across the Cortadera project may include further verification drilling, sampling, assaying and QA/QC. Other further work may also include mapping, surface sampling, ground or airborne geophysics as well as in-fill or exploratory drilling. |